

CROWDSTOPPER

PRODUCT SPECIFICATIONS

Overall Length:	8' 6" (8' 3" when interlocked)
Overall Height:	43"
Weight:	57 lbs.
Material:	Galvanized Steel.
Main Frame:	Outside perimeter (main frame) is made of 1½" O.D. galvanized steel tubing, minimum 16 gauge. The outer frame is a single length of tubing without welds or deformation. Pipe is bent at right angles with a minimum of smooth deformation. Horizontal and vertical bars are at right angles to overall frame.
Grill:	19 equally-spaced bars inside vertical members, made of ½" O.D. galvanized steel tubing, minimum 16 gauge. Minimum of ½" weld at the top and at the bottom of each upright bar. 19 interior bars are 4½" apart, O.D. to O.D. The spacing between inside vertical members does not exceed 4¾" and meets all standard codes.
Locking:	Male-Female interlocking ends. Units join and unlock at one position (30 degrees). Male interlocking device is a minimum ⅝" diameter rod welded through main frame at both ends. Male/Female connections have enough clearance to allow for uneven ground, a minimum of ½" on top and bottom when connected.
Feet:	Two (2) bolt on flat feet ½" x 2" flat steel bar with 1¼" O.D. 14 galvanized stem, or, two (2) bolt on bridge feet 1½" O.D. galvanized steel, 16 gauge, with ¼" O.D. galvanized stem.
Finish:	Entire panel is hot-dip zinc-galvanized after welding conforming to Marine specifications. Every barrier is filed after galvanizing so that burrs from galvanizing are filed smooth and there are no sharp points.
Finishes:	Galvanized steel, powder-coated black, powder-coated orange
Warranty:	3-year warranty against manufacturer's defects.



Signature Fencing & Flooring Systems, LLC
50 East 42nd Street • 14th Floor
New York, NY 10017
Toll Free: 800-569-2751 • 212-953-1116 • Fax: 212-953-1117
Flooring: www.eventdeck.com • Fencing: www.signaturefencing.com