



PRODUCT SPECIFICATIONS

Description: SuperScreen windscreen and privacy screen is the perfect addition to any facility. Used to provide shade, delineate areas, control wind, provide additional privacy and security, or create a neutral background for sports and other activities, Signature’s SuperScreen is the choice of prestigious organizations nationwide.

Item Number	Shade %	Construction	Weight (oz/sq.yd.)
PSA	90%	Woven	7.7
PSB	85%	Woven	4.8
PSC	92%	Woven	5.6
PSD	80%	Weft Insert	7.3
PSE	90%	Knitted	5.5
PSH	Complete Blockage	Vinyl	16

Material: **PSA, PSB, PSC, PSE:** 100% Polypropylene.
PSD: PVC-coated polyester fabric.
PSH: Solid Vinyl.

Colors: **PSA:** Black.
PSB, PSC: Forest Green, Black.
PSD: Forest Green, Kelly Green, Yellow, Royal Blue, Navy Blue, Carolina Blue, Red, Burgundy, Purple, Orange, Brown, Tan, Black, Gray, White.
PSE: Hunter Green, Royal Blue, Black.
PSH: Forest Green, Royal Blue, Red, Gray, Tan.

Standard Height: **PSA:** 6ft, 9ft, 12ft
PSB, PSC, PSD: 6ft, 9ft
PSE: 44”, 70”, 92”, 106”
PSH: 5ft

- Features:**
- a) Attaches to any fence providing a practical and economical solution.
 - b) Large color, weave and fabric selection to meet any need.
 - c) Maximum UV sunlight protection.
 - d) Ultra-strong 6-ply construction at the hem.
 - e) ½ - 1” wide hems sewn with 4-ply black polyester thread (excluding PSER rolls & PSH).
 - f) Brass-tooth grommets spaced 18” apart on all sides (excluding PSER rolls).
 - g) Center lacing lip standard for panels over 6ft high.
 - h) PSER rolls have woven eyelets (instead of the brass tooth grommets).

	PSA	PSB	PSC	PSD	PSE
Tensile Strength: ASTM-01682	445x375	265x140	360x190	213x218	97x280
Tear Strength: ASTM-D226	185x100	120x65	110x70	120x120	66x96
UltraViolet Resistance: % of tensile strength retained after 5,000 hrs.	90%	87%	90%	83%	88%

	PSH	
Tensile Strength:	5100 (Grab):	275 Wrap 230 Fill
	5102 (Strip):	180 Wrap 165 Fill
Tear Strength:	5134 (Tongue):	70 Wrap 60 Fill
Adhesion:	5970 (lbs./2"):	20
Flame Resistance:	5903 (Self Extinguishing):	Pass
Hydrostatic:	5512:	425
Cold Crack:	5874:	-40
Warranty:	2 years.	

